

CURVE LED WALL PACK 26W

Model No. CUR26W



Features & Options

- UL wet listed die-cast aluminum construction with tempered flat glass lens complete with stainless steel hardware.
- Mounts to standard 4 inch square electrical junction boxes. Alternate junction box mounting possible via universal mounting ring. Ingress resistant gasket included.
- 90 degree adjustability of beam angle with full cut off option
- Citizen® COB LED's and YG® driver technology
- Precision die cast
- Wall, post or bollard mount
- Dimming options available
- IP65 rated fixture for outdoor use
- Chip and fade resistant powder coat finish in many colors
- Highly specular forward throw reflector
- Industrial grade, Button type photocell
- Easy installation with hands free mounting
- Dark sky compliant mounting

Delivered Lumens 30K	
Delivered Lumens 40K	2470
Delivered Lumens 50K	3566
Efficacy lm/w	92
CRI	80
Dimmable	yes
Equivalent to	100W
Rated Life	50,000 HOURS
Input Voltage	120-277V
Input Frequency	50/60HZ
Power Factor	>0.9
Watts	26W
Dimensions (LxHxW)	7.21" X 4.20" X 5.53"
Operating Temperatures	-30C~40C
Environment	Wet Location IP65
Certification	UL, DLC
Warranty	5 Year Limited Warranty

